

LC 25 - 9601065


DATA SHEET







Main Accessories	LC 25		
Minor Spare Part Kit	K9601065		
Major Spare Part Kit	K9601065/1		
Shock Mounts	Fitted		
Inlet Filter	9001024		
Inlet Filter Element	1801017		
Outlet Filter	9001057		
Outlet Filter Element	1803009		



PRODUCT DESCRIPTION:

The LC.25 pump is equipped with:

- Oil check valve
- Exhaust mist eliminator
- Automatic floating oil recovery valve
- Adjustable inlet fitting
- Continuously working gas ballast
- Shock mounts
- Thermal protector (1~ only)

Compact design, low noise level, ease of oil check and refill and simplified maintenance operation, are the main features of this series. The damping and recovery system, equipped with a by-pass, together with the new float type oil recovery valve, ensures the absence of oil vapors at the outlet. Moreover, a sealing device prevents the oil from being sucked back should the pump stops under vacuum. The standard version is suitable for continuous operation within a pressure range from 400 to 0,5 mbar (Abs.).

MAIN APPLICATION FIELDS:

Vacuum packing machines; precious metal vacuum casting machines; dental field; graphic and paper industry; CNC marble and glass machines; vacuum lifting machines; garage equipment.

NOTE: Graph shows inlet pressure at a temperature of 68° F (tolerance ±10%)	LC 25			
Part Number	9601065/MX	9601065/MA	9601065/SG	
Voltage	110-115	220-240	208-230/460	
Nominal Capacity	17.1 CFM			
Total Final Pressure (Abs.)	29.91 inHg / .4 Torr			
Motor Power	1.0 HP (1~) 1.		2 HP (3~)	
Nominal r.p.m.	1700			
Noise Level dB(A)	59			
Weight	55 Lbs. (1~)		58 Lbs. (3~)	
Oil Type	SW 60			
Oil Quantity	1 Liter			
Pump Intake/Outlet	1/2"/ 1/2"			
Operating Temperature	185°F - 194°F			
Dimensions	15" X 8.5" X 5"			

Please contact the Manufacturer if environmental conditions are different from those prescribed.

YOUR VACUUM PROFESSIONALS